

NEW EATON DRIVE MOTORS:

MUSTANG #140850, EATON #112-1306-006 FOR MODEL 2050

MUSTANG #140849, EATON #112-1307-006 FOR MODELS 2060, 2070

CASE DRAIN / SHUTTLE OUTLET PORT

2050:
INSTALL EXISTING 230-32702 BEADED 3/8"
HOSE FITTING (WITH ORIFICE), AND
CONNECT HOSE ROUTED TO TANK FITTING
FROM EACH MOTOR AS BEFORE.

2060, 2070:

INSTALL EXISTING O-RING / JIC FLARE
FITTINGS, CONNECT JUMPER HOSE
BETWEEN MOTORS, AND CONNECT
RETURN HOSE ROUTED FROM LEFT
MOTOR TO FLOW CONTROL VALVE ON
HYDRO PUMP CASE FITTING SAME AS
SHUTTLE LINE SYSTEM WAS PLUMBED
BEFORE.

REMOVE SECOND SET OF EXISTING CASE
DRAIN LINES THAT WERE PLUMBED TO
TANK FITTING BEFORE. CAP TANK FITTING
WITH 3/16 JIC CAP (MUSTANG #230-18130
GEHL #076879 OR EQUIVALENT).

THESE OTHER PORTS NOT USED-
LEAVE PLUGGED

